


# WESTERN STATES METAL ROOFING



901 W. Watkins St., Phoenix, AZ 85007  
(855) 426-7836 | cortenroofing.com

## 1/2" CORRUGATED

Available in A606-4 (aka Corten®) or Bare Cold Rolled Steel.  
A606-4 Custom Order Only. Bare Cold Rolled in Stock.



## SPECIFICATIONS

**Material Type:** 1/2" Corrugated

**Rib Distance (Pitch):** 2.67" Pitch

**Rib Height:** 1/2"

**Available Gauges:**

- **A606-4 (aka Corten®):** 22 (Custom Order Only)
- **Bare Cold Rolled:** 22 (In Stock)

**Substrate:** A606-4 or Bare Cold Rolled

**Fasteners:** Exposed

**Panel Length:** 1' to 52'

**Recommended Minimum Roof Slope:** 3/12

**Installation:** Over a solid substrate



## RECOMMENDATIONS AND CAUTIONS

- A606-4 and Bare Steel performs best in environments with low humidity
- Load calculations and load tables DO NOT APPLY TO ANY A606 OR BARE STEEL PRODUCT.
- A606-4 should not be used with dissimilar metals other than stainless steel. This will decrease the lifespan of the product.
- Screws and clips for A606-4/Corten MUST be stainless steel. Screw head will be painted brown.
- Roofing Underlayment Should be a HIGH TEMPERATURE UNDERLAYMENT.
- Minimum roof slope 3:12 recommended.
- Not recommended near salt spray environments and frequent rain locations as it will shorten the life expectancy of the products.
- Acid washing will degrade steel performance.
- Rust runoff will likely stain the surrounding surfaces.
- NO WARRANTIES FOR THESE PRODUCTS

*Material does not arrive pre-rusted. Panel will rust naturally with exposure to the weather. Use stainless steel fasteners with a painted brown screw head.*